

# Desktop Virtualization Made Simple

Part Number: 6872v, 6817v, 6818v

## 6800 Series Thin Clients for VDI *Enterprise Class*

The 6800 Series is 10ZiG's next generation Thin Client. This Series has all the features of a traditional PC, incorporating a future proof hardware design while still maintaining high energy efficiency, resulting in the ability to expand the use cases for this Series all while maintaining an overall reduction in power.

The 6800 Series has been designed for businesses of all types and sizes. These Thin Clients have dual DVI video ports, optional legacy ports and a PCIe expansion slot which gives you the ability to add additional connection or video ports to the unit as your needs evolve. This series uses the AMD Embedded G-Series Dual Core Processor to achieve a high performance workstation.



- ▶ Supports High End Graphics
- ▶ AMD Radeon HD GPU
- ▶ Dual/Quad Monitor Capabilities
- ▶ Internal Wireless (Optional)
- ▶ FREE Centralized Management
- ▶ Embedded Lockdown Manager (WE8)
- ▶ Legacy Serial/Parallel Ports Available
- ▶ Support for USB 2.0 and USB 3.0

vmware

teradici  
PCoIP

CITRIX

HDX

Microsoft

Quest®  
vWorkspace

amazon  
web services™

redhat

2X

Americas  
EMEA  
APAC

P: 866-865-5250  
P: +44 (0) 116 214 8650  
P: 1300 768 799

E: info@10ZiG.com  
E: info@10ZiG.eu  
E: info@10ZiG.com.au

W: www.10ZiG.com

# 6800 Series Thin Clients for VDI

## 6800 Series Model

System	
Management	10ZiG Manager
Form Factor	Small
Processor	AMD Dual Core 1.65GHz
Chipset	AMD Embedded G-Series T56E/T56N
Dimensions	
Device	2.2"(W) x 9"(H) x 8.2"(D)
Weight	3.7 lbs
Connections	
Ports	USB x 6 (USB 2.0 x 4, USB 3.0 x 2), Serial Port x 1, PS2 x 1 - (Optional Parallel & additional Serial Port via PCIe Card)
Video/Audio	DVI x 2, Line-Out x 1, Internal Speaker x 1 (Optional additional DVI x 2)
Networking	
Wireless	Optional internal wireless a/b/g/n
Ethernet	RJ-45 10/100/1000 Base-T
Environmental	
Operating Temp.	32-95F (0-25C), 20-80% non-condensing humidity
Power	16 Watt Consumption, 48 Watt, DC-12V/4A External Power Adapter
WARRANTY: All Thin Clients include a 3-Year Advanced Exchange Warranty	



### SPECIFICATIONS

1. Power Button (LED inside)
2. HDD LED
3. Network Light
4. Mic In
5. Audio Out
6. Smart Card Reader (optional)
7. USB 2.0 Ports (x2)
8. Speaker
9. PS/2 Port
10. USB 3.0 Ports (x2)
11. USB 2.0 Ports (x2)
12. Ethernet 10/100/1000
13. PCI Expansion Slot
14. DVI-D Socket
15. DVI-I Socket
16. Serial Port
17. DC Jack
18. Kensington Lock

	6872v	6817v	6818v
<b>Operating System</b>	10ZiG PEAKos (Linux)	WES7	WE8
Memory			
RAM	MIN: 2GB MAX: 4GB	MIN: 2GB MAX: 4GB	MIN: 2GB MAX: 4GB
Storage	MIN: 1GB MAX: 128GB	MIN: 16GB MAX: 128GB	MIN: 16GB MAX: 128GB
Software			
Software Applications	Firefox, Citrix Receiver, RDP, Sun JVM, VNC	Internet Explorer, Citrix Receiver, RDP, VNC	Internet Explorer, Citrix Receiver, RDP, VNC
VDI Connection Brokers Supported	Citrix XenDesktop & VDI-In-a-Box w/ HDX, VMware Horizon View w/ PCoIP, RedHat, 2X, vWorkspace	Citrix XenDesktop & VDI-In-a-Box w/ HDX, VMware Horizon View w/ PCoIP, RedHat, 2X, vWorkspace, Microsoft	Citrix XenDesktop & VDI-In-a-Box w/ HDX, VMware Horizon View w/ PCoIP, RedHat, 2X, vWorkspace, Microsoft